

For professional use only Issue date: July 2010 Superseded TDS: February 2009



Kapci 100 1K Undercoat

Product description

Kapci 100 is 1K polyvinylchloride-epoxy based undercoat designed to protect car underbody from stone chipping and corrosion. It can be also applied over the body floor and other metal parts. Kapci 100 gives anticorrosion properties, excellent adhesion and chemical resistance.

Suitable substrates

Kapci 100 undercoat should be applied over rust free and degreased bare metal. For longer resistance to corrosion it is recommended applying any Kapci anticorrosive primer (Kapci 810/Kapci 850/Kapci 880) prior to undercoating with Kapci 100.



Kapci Car Refinishes System

These products are for the professional painting of automotive vehicles only after reference to the manufacturer's Material Safety Data Sheets

Product	Kapci 100
Thinner	Kapci 525
	Bare metal should be degreased with Kapci 606 degreaser. Painted surfaces should be degreased with Kapci 605 degreaser.
	By weight: Add 20% Kapci 525 thinner;
	Use the special UB gun for underbody products. Nozzle: 4-5mm; Pressure:4-5 bar Apply in 1-2 coats.
	Air dry at 20°C Dust free: 40-50 min Touch dry: 3-5 h Hard dry: 24 h

Health and Safety

1. For full Health and Safety information please refer to Material Safety Data Sheet;

2. Observe the precautionary notices displayed on the container;

3. Goggles and suitable protective equipment must be worn while using these products;

4. Good ventilation must be provided in the working environment;